

Brite Zinc, Gallon Item# 1008407

Product Description Zinc-rich top coat (primer) for ferrous and non-ferrous

surfaces. One step color matches the shiny look of hot dip galvanizing. 69% zinc metal. Covers 570 square feet. Meets ASTM-A780 standard for corrosion protection.

Color Gray

Applications For parts and assemblies to be top-coated.

Unit Package Description 3.78 Liter Metal Pail

Brand Weld-Aid

Generic Description 1 Corrosion Inhibitor

Net Fill 3.78 Liter

UPC Code 731592100068

Unit Dimensions 37.75H x 16.51W x 16.51D cm

Units Per Case 1

Case Dimensions 37.75H x 16.51W x 16.51D cm

Cases Per Pallet 80

Case Weight 9.97 kg

Appearance Silver Liquid

Flash point (F) 45°F Flash point (C) 7.2°C Spec Gravity Concentrate 1.43

Plastic Safe Not Determined

Evaporation Rate Slow

Dry Time - Fully Dry 24 Hours

Dry Time - Tack Free 15 to 30 minutes at 70°F(21°C)

Recoat 15 to 30 Minutes

Coverage 570 square feet at 1 mil thickness (174m2)

Working Temp (F) Not Determined Working Temp (C) Not Determined

Propellant None

Last revised: 6/2/2020

Page 1 of 2





Military Specification

MIL-P-26915B, Mil-P-46105

Number

DOT Proper Shipping Name Paint Related Materials, Limited Quantity

Restricted from Sale In: Not for sale in the United States.

Last revised: 6/2/2020

Page 2 of 2

