

WIRE ARMOUR™

PROFESSIONAL ELECTRICAL TAPE

When performance matters, count on WireArmour™ Electrical Tape from IDEAL Electrical to get the job done.



DESIGN | SIMPLIFY

IDEAL® Electrical is the Electrician's Champion™ and we design tools and supplies to simplify each job while handling the most challenging environments.

THE ELECTRICIAN'S
CHAMPION™



Special Use Tape

Linerless Rubber Tape

- Primary insulation up to 69kV
- Linerless ethylene rubber
- Excellent conformability to complex shapes
- Moisture, corrosion, and chemical resistant
- High thermal conductivity allowing heat to dissipate from joint
- Overload temperature: 266°F
- Elongation: 890%



Part No.	Dimensions	UPC Code
46-130C-3/4x30	3/4" x 0.03" x 30'	783250809844
46-130C-1x30	1" x 0.03" x 30'	783250809875
46-130C-1.5x30	1-1/2" x 0.03" x 30'	783250809851
46-130C-2x30	2" x 0.03" x 30'	783250809868

Rubber Mastic Tape

- Primary insulation up to 2kV
- Insulating and moisture sealing splices and terminations
- Moisture, corrosion and chemical resistant
- Suitable for direct burial and overhead applications
- Overload Temperature: 266°F
- Elongation: 890%



Part No.	Dimensions	UPC
46-2228-1x10	1" x 0.065" x 10'	783250809882

Mastic Pads

- Primary insulation up to 1kV
- Superior adhesion and dielectric strength
- Sealing and insulating for buried, submerged or overhead electrical connections
- Resistant to UV rays and impermeable to ozone, water, soil, dirt and corrosive chemicals
- Overload temperature: 266°F
- Package of 10



Part No.	Dimensions	UPC
46-2200-6.5x4	6-1/2" x 0.13" x 4"	783250810284

Corrosion Tape

- Protects pipe, joints, conduit and couplings in overhead or direct burial applications
- Highly resistant to sun, water, oil, acids, alkalis, and corrosive chemicals
- Bacteria and fungus resistant
- Pressure sensitive
- Thickness: 10mil



Part No.	Dimensions	UPC Code
46-50-UNPRINT-2	2" x 0.01" x 100'	783250809981