

GENERAL PURPOSE WATER HOSE

Water

G221 & 222

G221 and G222 are versatile EPDM rubber hoses. They are among our most popular hoses and find widespread use in industrial, agricultural, construction, and marine applications. G221 is a flexible and lightweight two-spiral hose, while G222 is a more robust four-spiral product. Multi-Purpose is used for air tools, nailers, staplers, jackhammers, and also as a hot or cold water washdown, heavy-duty heater, or low pressure agricultural spray hose.

G221 & G222... MULTI-PURPOSE

Tube: Black, limited oil-resistant EPDM rubber.

Reinforcement: High-tensile spiralled yarn; two spirals in G221 and four spirals in G222.

Cover: Smooth, red, abrasion and weather resistant EPDM rubber.

Temperature Range: -40°C (-40°F) to 95°C (203°F).

I.D.	Part Number	O.D.	Working Pressure	Weight per ft	PRICE PER FOOT			Approx Reel Length
					Cut	250 ft	700 ft	
1/4"	G221-025	0.50"	200 psi	0.09 lb	\$ 1.05		\$ 0.73	700 ft
3/8	G221-038	0.69	200	0.16	1.25		0.91	700
1/2	G221-050	0.88	200	0.25	1.45		1.22	700
1/4	G222-025	0.59	250	0.12	1.25	1.02	0.92	250 or 700
5/16	G222-031	0.63	250	0.14	1.80		1.38	700
3/8	G222-038	0.69	250	0.17	1.50	1.15	1.06	250 or 700
1/2	G222-050	0.84	250	0.25	2.00	1.60	1.50	250 or 700
5/8	G222-063	1.00	250	0.30	2.55		2.00	700
3/4	G222-075	1.16	250	0.38	2.80	2.20	2.00	250 or 700
1	G222-100	1.44	200	0.51	3.40	3.00	2.75	250 or 700
1 1/4	G222-125	1.78	200	0.81	6.10		5.10	500
1 1/2	G222-150	2.03	200	0.95	7.10		6.40	400
2	G222-200	2.50	200	1.13	10.20		9.80	250

For filling tankers with potable water from fire hydrants, we stock a food grade fire hose. See G1942BP in the Fire Hose section.



Pureflex® is designed for use where water main service is disrupted and temporary bypass hoses are used to supply drinking water to homes and businesses. The tube compound meets the toughest standards for potable water applications and will not transfer an odor or taste to the water. In addition, the tube in G1031 is less porous than rubber, and therefore is easier to flush and clean after use and prior to re-use. The heavy-duty construction limits kinking in hot weather and provides extra resistance to external wear and abuse.

G1031... PUREFLEX®

HIGH PURITY POTABLE WATER BY-PASS HOSE

Tube: Smooth, white, silicone and phthalate free PVC compound that complies with FDA (CFR title 21, parts 170-199), NSF-61, and California Proposition 65.

Reinforcement: Spiral layers of high tensile yarn.

Cover: Smooth, blue, abrasion and weather resistant PVC compound.

Temperature Range: -25°C (-13°F) to 65°C (150°F)

G1031

I.D.	Part Number	O.D.	Working Pressure		Weight per ft	PRICE PER FOOT		Coil Length
			at 20°C	at 50°C		Cut	Std Length	
3/4"	G1031-075	1.13"	250 psi	110 psi	0.33 lb	\$ 3.15	\$ 2.75	500 ft