

Dyna-Pak E6 Lanyards



CERTIFIED BY CSA CANADA

This lanyard is specifically designed for fall arrest purposes for workers weighing between 200-386 lbs. With many hardware options and webbing types, it will provide you with the best option to best suit your specific application. It is very important for the user to calculate the fall clearance requirement when using a lanyard with an energy absorber. (SEE calculations on page 46)

LANYARDS FIXED LENGTH WITH "DYNA-PAK E6" ENERGY ABSORBER

PART NO.	MATERIAL	CONNECTOR HARNESS	CONNECTOR ANCHORAGE	LENGTH
SINGLE LEG LANYARD WITH E6 ENERGY ABSORBER				
FP73311/4	POLYESTER	FP6650HS	FP6650HS	4-5-6 FT
FP73313/4	POLYESTER	FP6650HS	FP5386HS	4-5-6 FT
FP73314/4	POLYESTER	FP6650HS	FP5395HS	4-5-6 FT
FP733AA/4	POLYESTER	FP6650ALL	FP6650ALL	4-5-6 FT
FP733AC/4	POLYESTER	FP6650ALL	FP5395ALL	4-5-6 FT
SINGLE LEG ADJUSTABLE LANYARD WITH E6 ENERGY ABSORBER				
FP73411/4	POLYESTER	FP6650HS	FP6650HS	4-5-6 FT
FP73413/4	POLYESTER	FP6650HS	FP5386HS	4-5-6 FT
FP73414/4	POLYESTER	FP6650HS	FP5395HS	4-5-6 FT
DOUBLE LEG Y-LANYARD WITH E6 ENERGY ABSORBER				
FP736111/4	POLYESTER	FP6650HS	FP6650HS (2)	4-5-6 FT
FP736133/4	POLYESTER	FP6650HS	FP5386HS (2)	4-5-6 FT
FP736144/4	POLYESTER	FP6650HS	FP5395HS (2)	4-5-6 FT
FP736AAA/4	POLYESTER	FP6650ALL	FP6650ALL (2)	4-5-6 FT
FP736ACC/4	POLYESTER	FP6650ALL	FP5395ALL (2)	4-5-6 FT
DOUBLE LEG ADJUSTABLE-LANYARD WITH E6 ENERGY ABSORBER				
FP737111/4	POLYESTER	FP6650HS	FP6650HS (2)	4-5-6 FT
FP737133/4	POLYESTER	FP6650HS	FP5386HS (2)	4-5-6 FT
FP737144/4	POLYESTER	FP6650HS	FP5395HS (2)	4-5-6 FT
FIXED & CONTINUOUS SINGLE LEG LANYARD WITH E6 ENERGY ABSORBER				
FP77311/4	2" POLYESTER WEBBING	FP6650HS	FP6650HS	4-5-6 FT
FP77313/4	2" POLYESTER WEBBING	FP6650HS	FP5386HS	4-5-6 FT
FP77314/4	2" POLYESTER WEBBING	FP6650HS	FP5395HS	4-5-6 FT

FP73311/4

FP733AC/4

FP73413/46

FP736111/6

FP736144/4

FP736ACC/4

FP77311/4