

# Wire Pulling Tools

## WireSpanner™ – Telescopic Pole 18'

**NEW!**

**SUPER ROD® SERIES**



- Extends to 18' (5.4 m) in 10 seconds!
- Easily retrieve cable from a distance without needing an extra pair of hands to shorten installation time.
- Large hook attachment pulls multiple wires easily.
- Friction-twist lock pole design stays locked in place.
- Lightweight resin slides easily over obstructions.
- Compact design retracts to 32" (813 mm) for easy storage.

SRS56036

Cat. No.	Compact Length	Extended Length	Weight
SRS56036	32" (813 mm)	18' (5.4 m)	2.75 lbs. (1.25 kg)

## Polymer Fish Rod Set with Glow-in-the-Dark Leaders

**SUPER ROD® SERIES**




- Non-conductive rods designed for working in confined spaces.
- Great for routing cables in wire racks and on short runs.
- Attachments glow in the dark for ease of use.
- Includes 14" (356 mm) rods of various flexibilities and illumination for a range of individual (or 56" (1.4 m) combined) wire pulling applications.
- Includes five Glow-in-the-Dark leaders (hook, bullet, mini-eyelet, domed-eyelet and Claw).
- Convenient storage tube protects the rods between use and fits easily into your bag or toolbox.

SRS56038

**NEW!**

5 Attachments Included



Cat. No.	Extended Length	Weight
SRS56038	56" (1.4 m)	.25 lbs. (0.11 kg)

## Magnetic Wire Pulling System

**NEW!**

**SUPER ROD® SERIES**

- This system allows you to effortlessly pull cable behind walls by yourself.
- Navigates through insulation and other obstructions.
- Perfect for routing cable between drywall and insulation or fixture installations.
- Swivel leader eyelet securely connects to most wires and mesh wire pulling grips.
- Non-marring nylon leader-pull with 20' (6.1 m) of heavy-duty nylon rope eyelet for wire tie-on.



SRS56037

Cat. No.	Rope Length	Weight
SRS56037	20' (6.1 m)	.40 (0.18 kg)

# Wire Pulling Lubricant

## Wire Pulling Foam Lubricant

- **NO DRIPS! NO STAINS! NO MESS!**
- One can equals one gallon or 4 quarts of wax/gel lubricants\*.
- Foam lubricant is applied directly into the conduit. No need to pre-coat wires.
- No-mess formula stays where it is applied, even in vertical conduit!
- Dissolves clean from hands and clothing.



\*Based on job site pulls with foam in 3/4" conduit when used as directed.

Cat. No.	Description	Net Weight
51100	Wire Pulling Foam Lubricant	19 oz.

**WARNING:**

- Contents under pressure. Do not expose container to direct sunlight or temperatures above 120°F. Do not transport or store near heat sources. Keep cans dry and away from sources of ignition. If frozen, gradually warm to room temperature.
- Do not use wet product on live circuits. Compound is electrically conductive before it dries.



51100

All dimensions are in inches and (millimeters) unless otherwise specified.



[www.kleintools.com](http://www.kleintools.com)

See page 296 for additional information on warnings.