

Hooks & Carabiners



CERTIFIED BY CSA CANADA

Hooks and carabiners offer a multitude of applications and all are available in various forms and sizes. They offer maximum protection and all offer double locking or auto locking closures. They are designed to give you the greatest ease of operation. All are approved for a maximum load of 5000 lbs (22kn) unless other wise specified.



FP6650



FP4651



FP9652



FP5386



FP5395



FP415



FP714



FP775



FP843

DOUBLE LOCKING SMALL ERGONOMIC SNAP HOOKS

PART NO.	CONSTRUCTION	OPENING	TYPE OF LOCK	CERTIFICATION
FP6650	FORGE STEEL	3/4" (19MM)	DOUBLE LOCKING	ANSI, CSA, CE
FP6650HS	FORGE STEEL	3/4" (19MM)	DOUBLE LOCKING HIGH PERFORMANCE	ANSI, CSA, CE
FP4651	FORGE STEEL/SWIVEL	3/4" (19MM)	DOUBLE LOCKING	ANSI, CSA, CE
FP9652	STAMPED STEEL	3/4" (19MM)	DOUBLE LOCKING	ANSI, CSA, CE
FP9652HS	STAMPED STEEL	3/4" (19MM)	DOUBLE LOCKING HIGH PERFORMANCE	ANSI, CSA, CE

DOUBLE LOCKING LARGE ERGONOMIC REBAR AND SCAFFOLD HOOKS

PART NO.	CONSTRUCTION	OPENING	TYPE OF LOCK	CERTIFICATION
FP5386	FORGE STEEL	1 3/4" (44MM)	DOUBLE LOCKING	ANSI, CSA, CE
FP5386HS	FORGE STEEL	1 3/4" (44MM)	DOUBLE LOCKING HIGH PERFORMANCE	ANSI, CSA, CE
FP5395	FORGE STEEL	2 1/2" (62.5MM)	DOUBLE LOCKING	ANSI, CSA, CE
FP5395HS	FORGE STEEL	2" (51MM)	DOUBLE LOCKING HIGH PERFORMANCE	ANSI, CSA, CE

TWIST LOCK CARABINER CONNECTOR

PART NO.	CONSTRUCTION	OPENING	TYPE OF LOCK	CERTIFICATION
FP714	ALLOY STEEL & HEAT TREATED PEAR SHAPE	2-1/4" (57MM)	AUTO-TWIST LOCK	ANSI, CSA, CE
FP415	ALLOY STEEL & HEAT TREATED "D" SHAPE	5/8" (16MM)	AUTO-TWIST LOCK	ANSI, CSA, CE
FP775	ALLOY STEEL & HEAT TREATED "D" SHAPE	1" (25MM)	AUTO-TWIST LOCK	ANSI, CSA, CE
FP843	ALLOY STEEL & HEAT TREATED "D" SHAPE	3/4" (19MM)	AUTO-TWIST LOCK	ANSI, CSA, CE